ZPMV8.E348420 - Wiring, Printed Certified for Canada - Component

Wiring, Printed Certified for Canada - Component

LEITON GMBH
Wolframstr. 96
BERLIN, 12105 Germany

E348420

	Cond Width				Max	Report						Max			
	Min	Min Edge	Cond Thk	SS/ DS/	Area Diam	Date After 2022-01-01	Surface Mount	Assembly Solder Process Temp	Solder Process	Solder Limits		Oper Temp	Flame	Meets UL796	C T
Type	mm	mm	mic	DSO	mm		Technology	°C	Cycles	°C	sec	°C	Class	DSR	I
Mass laminated (multilayered) printed wiring boards															
YF-4	0.06	0.18	17	DS	50.8	No	-	-	-	280	20	130	V-0	All	3
Multilayer printed wiring boards															
RI-5	0.08	0.08	18 Int:105	DS	63.5	No	-	-	-	280	20	120	V-0	All	*
YF-7	0.075	0.18	17 Int:68	DS	50.8	No	-	-	-	280	20	130	V-0	All	*
YF-M	0.06	0.18	17 Int:68	DS	50.8	No	-	-	-	280	20	130	V-0	All	3
Single Layer Metal Base Printed Wiring Board															
YF-5	0.13	0.2	34	SS	50.8	No	-	-	-	288	10	125	V-0	-	2
Single Layer Metal Base Printed Wiring Board, flammability only Recognition															
YF-6	-	-	-	SS	-	No	-	-	-	288	10	-	V-0	-	-
Single Layer Metal Base Printed Wiring Boards															
FP-AL	0.12	0.12	17	SS	50.8	No	-	-	-	288	20	130	V-0	All	*
RI-7	0.17	0.18	34	SS	63.5	No	-	-	-	288	20	120	V-0	-	0
Single layer printed wiring boards															
EL-C	0.23	0.38	16.5	DS	38.1	No	-	-	-	260	10	125	V-0	All	*

EL-D	0.23	0.38	16.5	DS	101.6	No	-	-	-	260	10	125	V-0	▲	*
EL-E	0.23	0.38	16.5	DS	101.6	No	-	-	-	260	10	125	V-0	▲	*
EL-S	0.23	0.38	16.5	DS	101.6	No	-	-	-	260	10	125	V-0	▲	*
FP-C	0.12	0.12	34	DS	38.1	No	-	-	-	280	20	130	V-0	All	*
FP-F	0.10	0.10	17	DS	76.2	No	-	-	-	280	20	130	V-0	All	*
RI-2	0.05	0.15	33	DS	50.8	No	-	-	-	280	10	105	V-0	All	*
RI-3	0.15	0.45	33	DS	50.8	No	-	-	-	280	10	120	V-0	All	3
RI-6	0.08	0.08	18	DS	63.5	No	-	-	-	280	20	120	V-0	All	*
YF-1	0.1	0.1	17	DS	50.8	No	-	-	-	288	20	130	V-0	All	3
YF-2	0.06	0.18	17	DS	50.8	No	-	-	-	280	20	130	V-0	All	3
YF-3	0.075	0.18	17	DS	50.8	No	-	-	-	280	20	130	V-0	All	*

* - CTI marking is optional and may be marked on the printed wiring board.

Marking: Company name or trademark LEITON PRINTED CIRCUITS , LEITON , LEITON , or file number and type designation and the Recognized Component Mark for Canada, . May be followed by a suffix to denote factory identification or flammability classification..

Last Updated on 2022-08-05

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2022 UL LLC."